

Lived Vision

# ENTRANCE DOORS PRIME MODELS

2024

SECURE SIDE ENTRANCE DOORS

PRIMEMODELS 2024

### WOOD MODELS









NTA1 wood type meranti colour RAL 7016 anthracite grey glazing Iso light Ug-value: 1,2 W/m<sup>2</sup>K

NTA 2 wood type meranti colour RAL 7016 anthracite grey

Ug-value: 1,1 W/m<sup>2</sup>K

NTA 3 wood type pine colour LAS-12-09 glazing Iso light Ug-value: 1,2 W/m<sup>2</sup>K

NTA7

glazing Iso light

colour RAL 9016 traffic white

U<sub>a</sub>-value: KF 404 S - 1,3 W/m<sup>2</sup>K

U<sub>a</sub>-value: KF 694 - 1,3 W/m<sup>2</sup>K

Ug-value: AT 65 - 2,0 W/m<sup>2</sup>K

NTA4 wood type pine colour LAS-12-09 glazing Iso light Ug-value: 1,3 W/m<sup>2</sup>K

# **upvc & Aluminium Models**



NTA 5 colour RAL 9016 traffic white glazing Iso light

U<sub>0</sub>-value: KF 404 S - 1,2 W/m<sup>2</sup>K U<sub>a</sub>-value: KF 694 - 1,3 W/m<sup>2</sup>K Ug-value: AT 65 - 1,9 W/m<sup>2</sup>K



U<sub>0</sub>-value: KF 404 S - 1,0 W/m<sup>2</sup>K Ug-value: KF 694 - 1,0 W/m<sup>2</sup>K Ug-value: AT 65 - 1,6 W/m<sup>2</sup>K





NTA 8 colour RAL 9016 traffic white glazing Iso light

U<sub>0</sub>-value: KF 404 S - 1,2 W/m<sup>2</sup>K U<sub>a</sub>-value: KF 694 - 1,1 W/m<sup>2</sup>K Ug-value: AT 65 - 1,8 W/m<sup>2</sup>K

PLEASE CONSIDER max. dimension 1100 x 2150 mm frame outer dimension Calculation basis Ud-value according to DIN EN ISO 10077-1 (door size 1230 x 2180 mm)

\* aluminium doors are in system AT 65

# your possibilities SAFETY TECHNOLOGY

# SECURITY AND SAFETY FOR YOUR HOME

As standard, all doors are already equipped with a multiple locking system and solid entrance door hinges. Particularly with rear entrances that are difficult to see, you should attach particular importance to a high level of burglary protection. We therefore recommend our secure side entrance doors with impact resistant P4A safety glazing, cylinder with drill protection and RC 2 tested panel. The handle set with cylinder cover and pull protection is ES 1 tested.


### ON REQUEST THE PLUS IN SAFETY

You can upgrade your side entrance door with the following safety components. You receive your aluminium side entrance door on request with a RC 2 test certificate.

### SAFETY COMPONENTS



J					S standard
	1	Hinge-side security: When the door is closed, the opposite wedges get caught. Prying on the hinge side is significantly more difficult.			
		(S) wood	(+) aluminium	+ uPVC	
	2	P4A safety glazing: One of the panes consists of a composite of two panes with integ security foil. This offers a significantly increased burglary protection			
		+ wood	(+) aluminium	+ uPVC	
	3	Burglar resistant panel: the construction of the panel complicates the breakthrough.			
		(+) wood	(+) aluminium	+ uPVC	
	4	Glass/panel additionally glued in: the glass/panel is held in the sash by the glass rod as standard. A plus in safety is provided by the adhesion. The glass/panel is glued to the sash with a special adhesive.			
		+ wood	+ aluminium	+ uPVC	
	5	Additional hinge: two solid hinges are supplemented by a third hinge. (+) wood (+) aluminium (\$) uPVC			
	6	Cylinder with drill protection and 5 reversable keys: The drill protection makes it difficult to drill out the cylinder.			
		+ wood	(+) aluminium	+ uPVC	





### ΝΟΤΕ

Our patented Keilfalz on the hinge side is an additional prying protection which fulfills RC 2 criteria.

+ possible

# COLOURS/GLAZING/ALSO AVAILABLE

### UPVC COLOURS\*



GOLDEN OAK



MAHAGONY

WOOD COLOURS\*

PINE



SILVER GREY

structured

ANTHRACITE GREY structured/smooth/matt

### ALUMINIUM COLOURS



You will find a selection of trend colours in the KNEER-SÜDFENSTER aluminium colour chart. Wood decors are not possible!

# GLAZING







CHINCHILLA white

MASTERCARRE white

SATINATO white

(one side) (Chincilla white, Mastercarre white, Satinato white)

(standard) (standard) (only possible in KF 694) (RAL-Design, DB and NCS-colours not possible)

(optional handle/handle, ES1 tested with drilling protection)

LAS-12-09



MERANTI RAL 7037 dusty grey



MERANTI RAL 7016 anthracite grey

### GLAZING

PINE

VSG 6 mm for entrance door Ornamental glazing

SYSTEM

System AT 78 wood type spruce / meranti

### COLOURS

Wood surface according to KNEER-SÜDFENSTER wood colour chart Wood outside grooved panel uPVC one-sided foiled uPVC two-sided foiled uPVC acryl colour outside Aluminium according to KNEER-SÜDFENSTER colour chart, no wood decors

### HANDLES

Handle set as shown

### SECURITY / MISCELLANEOUS

Hinge-side security P4A safety glazing / panell RC 2 tested Gluing the panel / glass with sash frame cylinder with emergency and danger function, drill protection and 5 keys Additional hinge Safety execution RC 2 for aluminium entrance doors

\* Excerpts from the KNEER-SÜDFENSTER colour chart



Lived Vision



Your KNEER-SÜDFENSTER specialized dealer:

Subject to printing errors, mistakes and amendments. © KNEER-SÜDFENSTER